

RTMS®

Sx-300 HD CAM



The RTMS Sx-300 with HD camera provides the user with visual setup confirmation, data capture and verification over a TCP/IP connection.

The IP camera supports a variety of picture resolutions and frame rates allowing the user to:

- Provide visibility from the detector to verify the accuracy of zone setup across all lanes.
- Simplified visual ground truth ability for deployment verification.
- Facilitate real-time visual traffic surveillance anywhere, anytime.
- Still image publication to ATMS and ATIS

TECHNICAL DATA

- Video Resolution: 1280 x 720, 704 x 576, 640 x 352, 320 x 192
- Video Compression: H.264
- Compression Rate: Variable Bit Rate (VBR) and Constant Bit Rate (CBR) from 512Kb/s to 5Mb/s
- Video Frame Rate: 1 to 30 frames per second
- Video Snapshot: JPEG
- Streaming Format: Real Time Streaming Protocol (RTSP) with two (2) independent streams
- Adjustment of Video: Brightness, contrast, saturation, sharpness and image quality via web browser
- System Interface: 10/100 Base-T Ethernet port
- Security: Password protected user interface



RTMS Sx-300 with IP camera provides visual verification during setup and data capture.



RTMS Sx-300 HD CAM

SPECIFICATION

Average Coverage (Radar)

The Sx-300 detection field of view covers the area defined by:

- Elevation angle
50 degrees
- Azimuth
12 degrees
- Range
0 to 76 m (0 to 250 ft)

Measurement Resolution

- Detection zones
up to 12 zones
- Detection range (increment)
0.4 m (1.3 ft)
- Zone width
2 to 7 m (7 - 20 ft)
- Time events
1.3 msec

Frequency Bands

- K band, model Sx-300 operates at high resolution in the 24 GHz band

Regulatory

- FCC
- CE ETSI EN 300 440-1, ETSI EN 300 440-2, ETSI EN 301 489-1, ETSI EN 301 489-3, ETSI EN 301 489-17
- Canadian CSA C108.8 - M1983

Interface

- Single MS type connector provides communications and output signals
- Data: volume, occupancy, speed, gap or headway, six vehicle classes, 85th percentile
- 8MB built-in memory for data storage
- Isolated configurable RS232/RS-485 port provides vehicle presence, per vehicle and statistical data
- Eight (8) optically isolated output pairs rated for 100mA and 24VDC for presence indication and dual-loop speed
- Bluetooth communication for setup, calibration and data access

Mechanical

- Unit is encased in a rugged, water-tight NEMA 4X & IP-67 polycarbonate enclosure
- Universal mounting bracket mountable on any structure. Tilts on three axes and is lockable.
- Size
21 x 21 x 16 cm (8 x 8 x 6 in)
- Weight
1.5 kg (3.5 lbs)

Power

- Operates on 12 - 24 VAC or VDC
3.6W max standard
12W max with IP camera option
- EN 61000-4-5

Maintainability

- Ultra reliable: MTBF (mean time between failures) designed for 90,000 hours (10 years)
- Self-test diagnostic software
- Quick replacement
- Firmware field upgradable

Environmental Conditions

- Temperature range
Radar: -34° to +74°C (-29° to 165°F)
Camera: -10° C to +60° C (14° F to 140° F)
For optimum image performance
- NEMA TS2: 2003
- Wind
Up to 190 km/hr (120 mph)
- IP 67 compliant

Warranty

- Five-year warranty

CONTACTS

World Headquarters

500 Spruce Tree Centre
1600 University Avenue West
St. Paul, MN 55104 USA
Phone: +1.651.603.7700
Fax: +1.651.305.6402
info@imagesensing.com
imagesensing.com

Image Sensing Systems Canada

130 Bridgeland Avenue
Suite 201
Toronto, ON M6A 1Z4
Canada
Phone +1.416.785.9248
Fax +1.416.785.9332
sales@imagesensing.com
imagesensing.com



Precision decisions.

imagesensing.com

Due to ISS' continuous efforts to develop the products that are most responsive to our customers needs, the above specifications are subject to change. To verify the current information, please visit the Image Sensing Systems website.

©2018 Image Sensing Systems, Inc. Part Number:3075-1 Rev 180507